

SEAL SERVICE, S. A. DE C. V.

DIAMETRO EXTERIOR	DIAMETRO INTERIOR	PESO APROX. TFE VIRGEN
(plg.)	(plg.)	LONG. 14"
1"	SOLIDO	0.500 KG
	1/2"	0.395 KG
1-1/4"	SOLIDO	0.820 KG
	1/2"	0.780 KG
	5/8"	0.725 KG
	3/4"	0.660 KG
1-1/2"	SOLIDO	1.080 KG
	3/4"	0.975 KG
	7/8"	0.895 KG
1-5/8"	SOLIDO	1.250 KG
	1/2"	1.180 KG
	3/4"	1.060 KG
	7/8"	0.980 KG
	1"	0.890 KG
1-3/4"	SOLIDO	1.370 KG
	7/8"	1.070 KG
	1"	0.980 KG
1-7/8"	SOLIDO	1.550 KG
	*3/4"	1.340 KG
	7/8"	1.260 KG
	1"	1.185 KG
	1-1/4"	*0.950 KG
2"	SOLIDO	1.900 KG
	3/4"	1.550 KG
	7/8"	1.450 KG
	1"	1.400 KG
	1-1/4"	1.260 KG
	1-1/2"	1.180 KG

DIAMETRO EXTERIOR	DIAMETRO INTERIOR	PESO APROX. TFE VIRGEN
(plg.)	(plg.)	LONG. 14"
2-1/4"	SOLIDO	2.330 KG
	3/4"	2.200 KG
	*7/8"	2.130 KG
	1"	1.850 KG
	1-1/4"	1.750 KG
2-1/2"	1-1/2"	1.600 KG
	SOLIDO	2.900 KG
	*5/8"	2.790 KG
	3/4"	2.720 KG
	7/8"	2.650 KG
	1"	2.400 KG
	1-1/4"	2.300 KG
	1-3/8"	2.200 KG
	1-1/2"	1.900 KG
	1-3/4"	1.750 KG
	1-7/8"	1.600 KG
	2"	1.270 KG
	SOLIDO	3.600 KG
	1"	3.150 KG
2-3/4"	1-1/2"	2.500 KG
	1-3/4"	2.300 KG
	1-7/8"	2.135 KG
	2"	1.950 KG
2-7/8"	SOLIDO	3.800 KG
	1"	3.355 KG
	1-1/4"	3.190 KG
	1-1/2"	2.800 KG
	1-3/4"	2.610 KG
	1-7/8"	2.350 KG
	2"	2.250 KG
	2-1/8"	2.045 KG
	2-1/4"	1.830 KG

SEAL SERVICE, S. A. DE C. V.

DIAMETRO EXTERIOR	DIAMETRO INTERIOR	PESO APROX. TFE VIRGEN
(plg.)	(plg.)	LONG. 14"
3"	SOLIDO	3.950 KG
	1"	3.500 KG
	1-1/4"	3.000 KG
	1-1/2"	2.950 KG
	1-3/4"	2.920 KG
	1-7/8"	2.600 KG
	2"	2.550 KG
	*2-1/4"	2.325 KG
	2-1/2"	1.650 KG
3-1/4"	SOLIDO	4.770 KG
	1"	4.380 KG
	1-1/4"	4.160 KG
	1-1/2"	3.900 KG
	1-3/4"	3.600 KG
	1-7/8"	3.400 KG
	2"	3.200 KG
	2-1/8"	3.000 KG
	2-1/4"	2.800 KG
	2-1/2"	2.330 KG
	2-5/8"	2.100 KG
3-1/2"	SOLIDO	5.240 KG
	1"	4.750 KG
	1-1/4"	4.650 KG
	1-1/2"	4.600 KG
	1-3/4"	4.280 KG
	1-7/8"	4.100 KG
	2"	3.615 KG
	2-1/4"	3.500 KG
	2-1/2"	3.000 KG
	2-5/8"	2.800 KG
	2-3/4"	2.500 KG

DIAMETRO EXTERIOR	DIAMETRO INTERIOR	PESO APROX. TFE VIRGEN
(plg.)	(plg.)	LONG. 14"
3-3/4"	SOLIDO	6.220 KG
	1-1/4"	5.620 KG
	1-1/2"	5.350 KG
	1-7/8"	4.800 KG
	2"	4.670 KG
	2"2-1/4"	4.250 KG
	2-1/2"	3.800 KG
	2-5/8"	3.540 KG
	3"	2.725 KG
	3-1/4"	2.110 KG
	3-5/16"	1.960 KG
4"	SOLIDO	6.700 KG
	1"	6.650 KG
	1-1/4"	6.420 KG
	1-1/2"	6.155 KG
	1-3/4"	5.840 KG
	1-7/8"	5.600 KG
	2"	5.400 KG
	2-1/4"	5.000 KG
	2-1/2"	4.500 KG
	2-3/4"	3.850 KG
	3"	3.500 KG
	3-3/8"	2.600 KG
	3-1/2"	2.260 KG
4-1/4"	SOLIDO	7.880 KG
	1-3/4"	6.690 KG
	1-7/8"	6.500 KG
	2"	6.325 KG
	2-1/4"	5.900 KG
	2-1/2"	5.450 KG
	3"	4.075 KG
	*3-1/2"	3.115 KG

SEAL SERVICE, S. A. DE C. V.

DIAMETRO EXTERIOR (plg.)	DIAMETRO INTERIOR (plg.)	PESO APROX. TFE VIRGEN LONG. 14"
4-1/2"	SOLIDO	8.800 KG
	1-1/4"	8.175 KG
	1-1/2"	7.900 KG
	1-3/4"	7.600 KG
	2"	7.200 KG
	2-1/2"	6.350 KG
	2-3/4"	5.840 KG
	3"	5.280 KG
	3-1/2"	4.000 KG
	3-3/4"	3.300 KG
4-3/4"	SOLIDO	9.730 KG
	2"	8.175 KG
	2-1/2"	7.300 KG
	2-3/4"	6.790 KG
	3"	6.230 KG
	3-1/4"	5.620 KG
	*3-1/2"	4.960 KG
	3-3/4"	4.260 KG
5"	SOLIDO	11.500 KG
	1-1/2"	10.900 KG
	1-7/8"	10.400 KG
	2"	10.220 KG
	2-1/8"	10.000 KG
	2-1/2"	9.340 KG
	2-3/4"	8.830 KG
	3"	8.270 KG
	3-1/4"	7.970 KG
	3-1/2"	7.000 KG
	3-3/4"	6.300 KG
	4"	4.800 KG
	4-1/4"	4.740 KG

DIAMETRO EXTERIOR (plg.)	DIAMETRO INTERIOR (plg.)	PESO APROX. TFE VIRGEN LONG. 14"
5-1/4"	SOLIDO	11.775 KG
	2-3/4"	8.830 KG
	3"	8.270 KG
	3-1/2"	7.000 KG
	3-3/4"	6.700 KG
	4"	5.540 KG
	4-1/4"	4.500 KG
	4-3/8"	4.300 KG
5-1/2"	SOLIDO	14.000 KG
	2"	12.450 KG
	2-1/4"	12.000 KG
	3"	10.500 KG
	3-1/2"	9.245 KG
	3-3/4"	8.540 KG
	4"	7.785 KG
	4-1/4"	6.980 KG
	4-3/8"	6.560 KG
	5"	4.280 KG
6" Y 6-1/4"	SOLIDO	17.000 KG
	1"	16.690 KG
	2"	15.530 KG
	2-1/2"	14.650 KG
	2-3/4"	14.140 KG
	3"	13.580 KG
	3-1/4"	12.970 KG
	3-1/2"	12.300 KG
	3-3/4"	11.600 KG
	4"	10.850 KG
	4-1/4"	10.050 KG
	4-3/8"	9.630 KG
	4-5/8"	8.750 KG
	5"	7.350 KG
	5-1/8"	6.860 KG
	5-1/2"	5.300 KG

SEAL SERVICE, S. A. DE C. V.

DIAMETRO EXTERIOR (plg.)	DIAMETRO INTERIOR (plg.)	PESO APROX. TFE VIRGEN LONG. 14"
6-3/4"	SOLIDO	19.000 KG
	3"	15.570 KG
	3-3/4"	13.600 KG
	4"	12.850 KG
	4-1/4"	12.000 KG
	4-5/8"	10.745 KG
	5"	9.345 KG
	5-1/8"	8.850 KG
	5-1/2"	7.300 KG
7"	SOLIDO	20.400 KG
	2"	18.900 KG
	3"	17.660 KG
	3-1/2"	16.400 KG
	4"	14.250 KG
	4-1/4"	13.430 KG
	5"	11.440 KG
	5-1/8"	10.940 KG
	5-1/4"	9.730 KG
	5-7/8"	7.730 KG
	6-1/8"	6.570 KG
7-1/2"	SOLIDO	24.900 KG
	1-3/4"	23.720 KG
	1-7/8"	23.540 KG
	3"	21.400 KG
	3-3/4"	19.430 KG
	4-3/8"	17.460 KG
	4-5/8"	16.580 KG
	5"	15.180 KG
	5-1/8"	14.680 KG
	6-1/8"	10.300 KG
	6-5/8"	7.830 KG

DIAMETRO EXTERIOR (plg.)	DIAMETRO INTERIOR (plg.)	PESO APROX. TFE VIRGEN LONG. 14"
8"	SOLIDO	28.000 KG
	3"	24.620 KG
	*3-1/2"	23.350 KG
	3-3/4"	22.650 KG
	4"	21.890 KG
	4-1/4"	21.000 KG
	5"	19.400 KG
	*5-1/2"	16.350 KG
	5-7/8"	14.690 KG
	6-5/8"	11.000 KG
	6-3/4"	10.380 KG
	7"	9.000 KG
8-1/2"	SOLIDO	31.530 KG
	3-1/2"	26.760 KG
	*4"	25.300 KG
	5"	21.800 KG
	5-1/2"	19.750 KG
	5-7/8"	18.000 KG
	6-5/8"	14.450 KG
	7"	12.450 KG
	7-3/8"	10.360 KG
9"	SOLIDO	35.130 KG
	3-3/4"	29.650 KG
	4-1/4"	28.100 KG
	5-1/8"	24.900 KG
	5-1/2"	23.350 KG
	6-1/8"	20.520 KG
	7"	16.000 KG
	7-3/8"	13.960 KG
	8"	10.200 KG

SEAL SERVICE, S. A. DE C. V.

DIAMETRO EXTERIOR	DIAMETRO INTERIOR	PESO APROX. TFE VIRGEN
(plg.)	(plg.)	LONG. 14"
10"	SOLIDO	43.950 KG
	3-3/4"	38.470 KG
	*5-1/2"	32.170 KG
	6"	29.930 KG
	6-1/8"	29.340 KG
	6-1/4"	28.730 KG
	7"	24.870 KG
	7-3/8"	22.770 KG
	8"	19.000 KG
	9-3/16"	10.640 KG
11"	SOLIDO	51.480 KG
	3-1/2"	46.700 KG
	4"	45.250 KG
	7"	32.400 KG
	8"	26.560 KG
	9-3/16"	18.175 KG
	9 -7/8"	12.550 KG
12"	SOLIDO	60.825 KG
	5-7/8"	47.380 KG
	7"	41.750 KG
	8"	35.910 KG
	9-3/16"	27.500 KG
	9 -7/8"	21.895 KG
13-1/2"	SOLIDO	79.000 KG
	7"	60.000 KG
	8-7/8"	48.380 KG
	9-7/8"	41.000 KG
	11"	32.000 KG
	11-3/4"	25.300 KG
15-1/2"	SOLIDO	99.600KG
	8"	74.700KG
	11"	52.540KG
	12-5/8"	37.600KG

DIAMETRO EXTERIOR	DIAMETRO INTERIOR	PESO APROX. TFE VIRGEN
(plg.)	(plg.)	LONG. 14"
16"	SOLIDO	97.300 KG
	6-1/4"	50.400 KG